



# Series 5400 Calendered Etched Glass Film

Series 5400 is a silver, intermediate, 4-mil (100 micron), calendered vinyl with pressure sensitive adhesive. It is designed to simulate an etched glass look when applied to various glass surfaces. This cost effective solution is easy to work with, and it provides added elegance to a design. Series 5400 can be used either indoors or outdoors. Indoor durability is 5 years. Outdoor durability is up to 3 years, depending on region.

## APPLICATIONS & FEATURES

- Low cost alternative.
- Excellent cutting and weeding.
- Ideal for interior and exterior applications on glass surfaces.

## PERFORMANCE & PHYSICAL DATA

PROPERTY	TEST METHODS	TYPICAL VALUE	
<b>SURFACE FINISH</b>	Gloss Meter 60° Reflection	15 - 20%	
<b>THICKNESS (INCLUDING ADHESIVE)</b>	Micrometer, Federal Bench Type	4-mil (100 micron)	
<b>TENSILE STRENGTH</b>	Tensile Tester with 2-in (51 mm) jaw separation; crosshead speed of 12in/min. (5.1 mm/s), web direction	> 12 lbf width	> 2.14 kg/cm width
<b>ELONGATION</b>	Instron Tensile Tester as above	≥ 150%	
<b>SHELF LIFE</b>	Free from excessive moisture, temperature, direct sunlight	1 Year from factory shipment	
<b>APPLICATION TEMPERATURE RANGE</b>	On clean, dry substrate	60°F to 90°F optimum	10°C to 30°C
<b>HUMIDITY RESISTANCE</b>	Applied to etched aluminum panels 24 hours prior to testing. 100% relative humidity 100° (38°) for 500 hours	TEST WILL BE COMPLETED AT END OF NOVEMBER 2012	
<b>DIMENSIONAL STABILITY</b>	158°F (70°C), 48 hours	0.015 – 0.035 in	0.508 – 0.889 mm
<b>PEEL ADHESION</b>	PSTC-1, 15 min	37 oz/in	0.413 kg/cm
<b>LINER RELEASE</b>	TLMI, 300 in/min (127 cm/min) 2 in (51 mm) wide sample	184 g/2 in	184 g/2 in

\*Standard Terms & Conditions Apply

Effective Date 11.12

USA: 2811 S. Harbor Blvd. Santa Ana, CA 92704 – Telephone: 800-854-0361 – Fax: 714-540-7190  
 Customer Service: Telephone: 800-232-7161 – Fax: 800-329-2756 – Technical Services: 877-275-6698

EUROPE: North Sea Building, Gevers Deynootweg 93, 4th Floor, 2586BK Den Haag, The Netherlands – Telephone: +31 (0) 70 354-4311 – Fax: +31 (0) 70 355-7721

INDIA: 4F1 Court Chambers, 35 - New Marines Lines, Mumbai 400 020 – Telephone: +91 99 6755-3895

[www.arlon.com](http://www.arlon.com)

## **TERMS & CONDITIONS**

*The following is made in lieu of all warranties expressed or implied:*

All statements, technical information and recommendations published by Arlon relating to Arlon products are based on tests believed to be reliable and within the accuracy of the equipment used to obtain the specific values. Their accuracy or completeness is not guaranteed and Arlon makes no warranty with regard thereto. Seller's and manufacturer's only responsibility shall be to replace any quantity of the product proved defective. Seller and manufacturer shall not be liable for injury, loss or damage, direct or consequential, arising out of use or the inability to use the product. Nor shall seller or manufacturer be liable for any costs or expenses incurred in the processing or printing on the product. Before using, user shall determine the suitability of the product for its intended use. User assumes all risk and liability of every nature in connection therewith. No statements or recommendations other than those contained in the technical information published by Arlon shall have force or effect unless contained in an agreement manually signed by the officers of seller and manufacturer.

**USA:** 2811 S. Harbor Blvd. Santa Ana, CA 92704 – Telephone: 800-854-0361 – Fax: 714-540-7190

Customer Service: Telephone: 800-232-7161 – Fax: 800-329-2756 – Technical Services: 877-275-6698

**EUROPE:** North Sea Building, Gevers Deynootweg 93, 4th Floor, 2586BK Den Haag, The Netherlands – Telephone: +31 (0) 70 354-4311 – Fax: +31 (0) 70 355-7721

**INDIA:** 4F1 Court Chambers, 35 - New Marines Lines, Mumbai 400 020 – Telephone: +91 99 6755-3895

[www.arlon.com](http://www.arlon.com)