

Technical Data Sheet

Issue date: 01/08/2014 Date last modification: 02/04/2015

# 08505 - RI-JET DECO-WALL 100 ASP32 WK 135

# Face Material

Matt white monomeric soft vinyl.

Type Monomeric Vinyl Colour and Finish Matt white

**VISCOM** - INK-JET DIGITAL

ISO-536 Weight 134 g/m<sup>2</sup> ±10% ISO 534-80 Thickness 100 µ ±10%

# Adhesive

Permanent adhesive with excellent adhesion on indoor wall. The adhesive has a very high peel adhesion and medium cohesion.

Reference ASP32

Permanent solvent based Type

Min. Appl. Temp. +5°C -30/+120 °C Service Temp. Shear Medium

12 N/25mm FINAT FTM9 Tack Final Adhesion FINAT FTM2 16 N/25mm

# Liner

One side siliconised clay coated Type

Kraft

Colour and Finish White

PP-032 - ISO Weight 135 g/m<sup>2</sup> 536

±10%

**Thickness** 145 µ ±10% ISO 534 DIN 53 147-64 Transparency n.a. %

### **Applications**

For walls interior decoration.

This PVC self adhesive material offers a cost effective solution to interior designer who are looking for a film to decorate internal walls or shop interior.

We advise an overlap of 1,5 cm when positioning the

Indoor durability 4 years unprinted material.

# **Printing Methods**

Printable with eco-solvent, solvent, UV and Latex ink-jet. Print and immediate cut is feasible.

Testing for suitability between media, printers and inks is always recommended prior to use.

#### Shelf life

36 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following STORAGE CONDITIONS:

- This material must be stored at a temperature of  $22^{\circ}C \pm 2^{\circ}C$  and  $50 \pm$ 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.



