

ChalkMate™ Permanent Black

Print Media

ChalkMate™ Permanent Black is a 7 mil (180µ) PVC film with a traditional black chalkboard finish with a permanent, pressure sensitive acrylic adhesive protected by a 1 side siliconized, 1 side PE coated white Kraft release liner.

Typical Applications

- Durable vinyl film that can be written on with standard chalk.
- Can be installed on most smooth surfaces.
- Ideal for fixture applications.
- Can be used to make unique, custom chalkboard decals from die cut shapes or designs.
- Popular for use in children's rooms, schools, daycare centers, and grocery stores as well as for use on pub menus or shopping mall advertising.
- ChalkMate™ Permanent Black has a Class 0 Fire Rating according to UK standards for surface spread of flame, making it perfect for applications in public areas that require compliance with strict fire regulations, such as airports, hotels and hospitals.

IMPORTANT NOTE:

Information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Follow the indications on the package, ask for the safety data sheets and always follow the indications contained therein.

Only the correct use of the product will allow satisfactory results. For this reason, Drytac is not responsible for improper use of the product, either by application or substrate applied to. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact Drytac at one of the phone numbers listed below.

Print Compatibility

- UV

Product Structure

Film	Black PVC	8 mil (204µ)
Adhesive	Acrylic (Pressure Sensitive)	
Release Liner	Siliconized 1 Side PE Coated Kraft	

Physical Characteristics

Film Thickness	7 mil (180µ)
Adhesive Layer	1 mil (24µ)
Film/Adhesive Ratio	7:1
UV Protection Factor	Not Applicable
Outdoor Durability	Not Applicable
Application Temperature	>41°F (5°C)
Service Temperature Range	-4°F to 203°F (-20°C to 95°C)
Shelf Life	Use within 1 year after opening original box
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity